






Fire Hose Cabinet Double Door

SS7560

Saudi Sicli Co, SASO approved Hose Reel Cabinets with 1" Hose and Hose Valve (Manual & Automatic) indigenously as per International standardes, such as B.S. (British) DIN (German). NFPA (American) with strict Quality Control ensuring the customer needs.

Cabinets are manufactured from Stainless Steel No. 316L of thickness 1.5mm to 2mm, which depends upon the use and consumer requirements. The cabinets are with all round edges without any sharp edges and burns, having different style of doors and type of cabinets like wall mounted recessed, Semi Recessed type as per architectural design engineer requirements.

	In	side Din	nension	s	
Surface Type			Recess Type		
Width	Height	Depth	Width	Height	Depth
1050	800	220	1050	800	220
mm	mm	mm	mm	mm	mm



FRONT Surface Type Model SS7560

4	Į.	1050 mm	35mm		
800 mm	0	0		Ф	
Щ	FF	RONT	36min SII	205	
			odel SS75		

SS7560 Surface Type
1" Ø x 30 m Long
Fire Hose Rubber
1" Ø Fog Nozzle
1.5" Ø Angle Valve
Full Stainless Steel Cabinet
Full Stainless Steel Door
Stainless Steel Finish
Hose Reel Drum

ľ	SS7560 Recess Type
	1" Ø x 30 m Long
	Fire Hose Rubber
	1" Ø Fog Nozzle
	1.5" Ø Angle Valve
	Steel Cabinet
	Full Stainless Steel Frame & Door
	Red Color with Stainless Steel Frame & Door
	Hose Reel Drum

Available Glass Types



Model - C



Model - V

Vertical Glass



Model - G





Hose Reel Drum manufactured from steel on hydraulic press with forming of ribs to give extra strength and avoid twisting. The outer rolled over to give a safe handling edge on the outer rims and better appearance.

Hose is made of rubber with working pressure 20 bars and bursting pressure 60 bar with standard red color

Cabinet Door Handle is Recessed type made of S. Steel base and turn handle chrome plated.

VALVE 1.5" size with 45° angle Brass Chrome finish

Nozzel available in the three types:

- ♦ Plastic nozzle three way to control with straight, spray and stop functions.
- Brass with chrome plated two ways to control with straight and stop functions.
- Brass nozzle plated Three ways to control with straight and stop funcitons.

Painting for cabinets is done by electrostatic power paint oven backed to temperatures between 160-200° C, for steel cabinets only to protect from Rust and to give good finish Painted red and other colors available upon request. Stainless steel Cabinets with hair line finish and mirro finish also available.

Operating Instructions are silk screen printed in English and Arabic language inside the cabinet doors.

