

As a result of the technical cooperation between Saudi Sicli and Cofem the SS200 fire detection control panel been produced in our factory in Jeddah This control panel is first Arabian product.



Conventional Fire Alarm Control Communicator

SS200



Introduction

SS200 conventional control panel has been designed meeting the EN54Standard, part 2, according to the last review, and successfully overcoming the most hard tests about environmental conditions, electrical conducted noises, electromagnetic upsets, vibrations, etc. according to UL standard requirements. SS200 control panel is based on micro processed technology.

Composition

- ◆ Display screen
- ◆ 24 LED that allows to see quickly the state of the control panel (Power supply, function, mode, Alarm and fault)
- ◆ Keyboard of 7 keys
- ◆ An external RESET entry is also available
- ◆ Power supply source, independent modules that generates the voltage of primary
- ◆ power supply of 30V with protection fuses
- ◆ The control panel has built in buzzer

Features

- ◆ Complies with: EN 54 Part 2 and 4
- ◆ CE marked
- ◆ UL Compatible
- ◆ Microprocessor – controlled
- ◆ Configurable control panel available in 4, 6 and 8 zones
- ◆ Relay module can be added if required
- ◆ Over - Voltage protection for all control components
- ◆ Each zone capacity 25 to 30 detectors
- ◆ It is compatible with almost all conventional detectors in market